
REVISION HISTORY

REV. DESCRIPTION DATE ECO BY



# NOTES:

- 1. THESE ARE FINISHED DIMENSIONS READY FOR THE LINER.
- 2. DIMENSIONS ARE FROM INSIDE POOL PANELS.
- ROPE AND FLOAT ASSEMBLY SHOULD BE INSTALLED IN ACCORDANCE WITH CURRENT ANSI/ASPS/ICC REGULATIONS
- HYDRA LINER TRACK FOR STEPS IS INSTALLED WITH THE BARB FACING THE RISER WALL ON THE STEP.

#### **EXCAVATION NOTES:**


- ROUGH EXCAVATION SHOULD BE 2" DEEPER IN EACH INSTANCE.
- . SOIL TO HAVE MINIMUM BEARING CAPACITY OF 1500 PSF.
- LOCATE TOP OF POOL AT LEAST 6" ABOVE THE SURROUNDING LAND ELEVATION.
- SEE "OVER DIG DETAIL" FOR EXCAVATION AROUND POOL.
- 9. FILL VOIDS UNDER BASE OF PANELS AND TAMP WELL.
- 10. BACK FILL WITH NON-EXPANSIVE MATERIAL.
- 11. FOLLOW ALL CURRENT ANSI / APSP / ICC GUIDELINES FOR RESIDENTIAL POOLS


## **IMPORTANT NOTES:**

THIS DOCUMENT IS FOR ILLUSTRATIVE PURPOSES ONLY. THE DEALER OR CONTRACTOR WHO SELLS OR INSTALLS YOUR POOL IS AN INDEPENDENT CONTRACTOR AND IS NOT AN AGENT OF THE MANUFACTURER. THE CONSTRUCTION METHODS ILLUSTRATED HERE ARE SUGGESTIONS AND APPLY ONLY TO NORMAL GROUND CONDITIONS. THERE MAY BE ADDITIONAL PRECAUTIONS AND/OR METHODS OF CONSTRUCTION. PROPER INSTALLATION IS THE RESPONSIBILITY OF THE DEALER/BUILDER/CONTRACTOR.

ITEM	FILE NAME	DESCRIPTION	CUSTOMER DRAWING#	VENDOR PART#	QTY.
1	BOLT, PACK	BOLT, FLANGE, 3/8-16 X 1", PACK (50)	HPS1916	HPS1916	7
2	SBRACE	BRACE, FOLD OVER WITH TURNBUCKLE, STEEL, HPSFOB	HPSFOB	HPSFOB	30
3	00017449	LAYOUT, 31' X 59', DUBAI, 8' DEEP, HS106N, LIGHT, 3-1084, 4-INLET, 600 SERIES	00017449		1
4	PANEL, STRAIGHT	PANEL, 1'-3" LONG, 600 SERIES	HPSC2	00010755	1
5	PANEL, STRAIGHT	PANEL, 1'-9 1\2" LONG, 600 SERIES	HPSCS2	00011454	1
6	PANEL, STRAIGHT	PANEL, 3' LONG, 600 SERIES	HPSD103P	00000643	1
7	PANEL, RADIUS	PANEL, 4' RADIUS, 3'- 1 3\4" LONG, 600 SERIES	HPSCR4	00003051	2
8	PANEL, RADIUS	PANEL, 4' RADIUS, 6'-3 3\8" LONG, 600 SERIES	HPSD4R	00000289	1
9	PANEL, RADIUS	PANEL, 8' RADIUS, 3'-2" LONG, 600 SERIES	HPSCR4	00006142	1
10	PANEL, RADIUS	PANEL, 8' RADIUS, 5' LONG, 600 SERIES	HPSD8R5	00001450	1
11	PANEL, RADIUS	PANEL, 8' RADIUS, 8' LONG, 1084, 600 SERIES	HPSD8R884	00000271	2
12	PANEL, RADIUS	PANEL, 8' RADIUS, 8' LONG, 600 SERIES	HPSD8R8	00000145	1
13	PANEL, RADIUS	PANEL, 8' RADIUS, 8' LONG, INLET, 600 SERIES	HPS8R8I	00000758	2
14	PANEL, RADIUS	PANEL, 9' RADIUS, 5' LONG, 600 SERIES	HPSD9R5	00000354	2
15	PANEL, RADIUS	PANEL, 9' RADIUS, 8' LONG, 1084, INLET, 600 SERIES	HPS9R884I	00003874	1
16	PANEL, RADIUS	PANEL, 9' RADIUS, 8' LONG, LIGHT, 600 SERIES	HPSD9R8L	00000398	1
17	PANEL, RADIUS	PANEL, 9' RADIUS, 8', INLET OR LED, 600 SERIES	HPS9R8I	00000275	1
18	PANEL, RR	PANEL, 9' REVERSE RADIUS, 1' LONG, 600 SERIES	HPSCRR2	00002000	1
19	PANEL, RR	PANEL, 9' REVERSE RADIUS, 4' LONG, 600 SERIES	HPSD9RR4	00000414	1
20	PANEL, RR	PANEL, 9' REVERSE RADIUS, 4'-2 3\4" LONG, 600 SERIES	HPSCRR5	00003043	2
21	PANEL, RR	PANEL, 9' REVERSE RADIUS, 7' LONG, 600 SERIES	HPSD9RR7	00000170	1
22	PANEL, RR	PANEL, 9' REVERSE RADIUS, 8' LONG, 600 SERIES	HPSD9RR8	00000436	6
23	HS106N	STEP, 8' RADIUS, 3 TREAD	HS106N	HS106N	1

	WEIGHT: 473851.0 lbs VOLUME:	DIVILINGIONS AILL IN INCITES	BUMPHREY	5/1/2014	HYDRA POOLS
ė:	Inch <sup>3</sup>	DECIMALS: X ± .1	DETAILED BY: BUMPHREY	DETAILED DATE: 1/30/2018	
NUMBE	HEAT TREAT:	XXX ± .001 XXXX ± .0005	LAST REVISED BY: bumphrey	LAST REVISED DATE: 1/30/2018	TITLE: LAYOUT, 31' X 59', DUBAI, 8' DEEP, HS106N, LIGHT, 3-1084, 4-INLET, 600 SERIES
49 49	FINISH:	ANGULAR: X ± 0.5	MATERIAL:		
174	TEXTURE:	THIRD ANGLE PROJECTION			PART NUMBER:   SCALE:   SIZE:
ENGINEERING DRAWING NUMBER: 00017449					00017449 196 SHEET: A
C:\PDMwr	rking\00017449				





Area: 1197.84ft ^2 Perimeter: 177.16ft Volume = 42668 US gallons

### NOTES:


- THESE ARE FINISHED DIMENSIONS READY FOR THE LINER.
- DIMENSIONS ARE FROM INSIDE POOL PANELS.
- ROPE AND FLOAT ASSEMBLY SHOULD BE INSTALLED IN ACCORDANCE WITH CURRENT ANSI/ASPS/ICC REGULATIONS
- HYDRA LINER TRACK FOR STEPS IS INSTALLED WITH THE BARB FACING THE RISER WALL ON THE

# EXCAVATION NOTES:

- ROUGH EXCAVATION SHOULD BE 2" DEEPER IN EACH INSTANCE.
- SOIL TO HAVE MINIMUM BEARING CAPACITY OF 1500 PSF.
- LOCATE TOP OF POOL AT LEAST 6" ABOVE THE SURROUNDING LAND ELEVATION.
- SEE "OVER DIG DETAIL" FOR EXCAVATION AROUND POOL.
- FILL VOIDS UNDER BASE OF PANELS AND TAMP WELL.
- 10. BACK FILL WITH NON-EXPANSIVE MATERIAL.
- FOLLOW ALL CURRENT ANSI / APSP / ICC GUIDELINES FOR RESIDENTIAL POOLS

#### IMPORTANT NOTES:

THIS DOCUMENT IS FOR ILLUSTRATIVE PURPOSES ONLY. THE DEALER OR CONTRACTOR WHO SELLS OR INSTALLS YOUR POOL IS AN INDEPENDENT CONTRACTOR AND IS NOT AN AGENT OF THE MANUFACTURER. THE CONSTRUCTION METHODS ILLUSTRATED HERE ARE SUGGESTIONS AND APPLY ONLY TO NORMAL GROUND CONDITIONS. THERE MAY BE ADDITIONAL PRECAUTIONS AND/OR METHODS OF CONSTRUCTION. PROPER INSTALLATION IS THE RESPONSIBILITY OF THE DEALER/BUILDER/CONTRACTOR.



WEIGHT:  Ibs   VOLUME:  Inch³     COLOR:  NA     HEAT TREAT:	TOLERANCES  DECIMALS: X ± .1  XX ± .01  XXX ± .001  XXXX + .0005	DEGIGINED DT.	9/12/2013  DETAILED DATE: 1/30/2018  LAST REVISED DATE: 1/30/2018	HYDRA POOLS  TITLE: LAYOUT, 31' X 59', DUBAI, 8' DEEP, HS106N, LIGHT, 3-1084, 4-INLET, 600 SERIES
COLOR: NA OPENING NO NA OPENING N	ANGULAR: X±0.5 THIRD ANGLE PROJECTION			PART NUMBER: SCALE: 1:96 SHEET: 2 OF 5 A

