

# P3-35

## 3-Channel Amplifier



### Specifications: P3-35

### Mounting hardware included

Frequency Response ( $\pm 0.5$ dB)	10 Hz - 20 kHz @ 1 Watt RMS 8 Ohms $> .1\%$ THD
Power Output	2 Channel - 50 watts RMS/CH $>1\%$ @ 8 ohms, 55 watts @ 4 ohms; 3 Channel - 35 watts RMS/CH $>1\%$ @ 8 ohms, 40 watts @ 4 ohms
Power Requirements	Input: 100-240VAC 50/60 Hz, UL-CUS, FCC, CE, TUV, SUD, PSB, PSE; Output: 32VDC @ 3.75A
Frequency EQ	+3 dB Switchable @ 120 Hz, 2 kHz, 8 kHz
Inputs	Stereo Mini Analog, Optical Digital, Bluetooth
Outputs	2 or 3 Channel Euroblock; Line Level Sub Out
Height (SM = Height)	31.75 mm / 1.25 in
Diameter (SM = Width)	99.06 mm / 3.9 in
Weight	0.42 kg / 0.93 lb
Regulatory - CE	approved
Regulatory - RoHS	Approved

### Description

Phase Technology's P3-35 mini-amp is a powerful and feature-rich amplifier in a small package.

The P3-35 features digital and analog inputs, Bluetooth® functionality (so you can stream content right from your smart phone), IR learning (so you can program your television remote to control the amp's volume), and even a line-level subwoofer output option, allowing you to integrate any powered subwoofer into your set-up. The P3-35 even features Dolby Digital® decoding, ensuring that you'll never lose the surround content in any Dolby Digital mixes.

The P3-35 amp measures only 1 ¼" by 4", so its small enough to fit behind a wall mounted TV and, when paired with any of Phase Technology's ultra-thin Teatro speakers, will create the perfect installation scenario for this powerful and feature-rich mini-amplifier.

### Patented Rockustics

### Technologies

Rockustics and MSE Audio Group constantly develop new technologies that enhance audio product performance. Rockustics innovations are protected by multiple U.S. and international patents, which explicitly cover Rockustics dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Rockustics resellers and end users.

### Technical Data and Specification Tools

#### Technical Data

SoundTube Entertainment strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at [www.soundtube.com](http://www.soundtube.com). Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers

SoundTubeSPEC™ - Proprietary speaker placement software

### Data Acquisition and Verification

All data for SoundTube speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

### Architectural Specifications

No specifications currently.

#### Rockustics

8005 W 110th Street, Suite 208  
Overland Park, KS 66210  
Phone 913.663.5600  
Fax 913.663.3200  
Toll Free (855) 663-5600  
<https://rockustics.mseaudio.com>  
All SoundTube products come with a 5-year limited warranty.

---

# P3-35

3-Channel Amplifier

