

SPF-25

5.25" 2-Way Surface-Mount Outdoor Speaker



Specifications: SPF-25

Mounting hardware included

Nominal Impedance	8 ohms
Sensitivity dB @ 2.83V/1M	89 dB
Frequency Response (1)	60 Hz - 20 kHz
Recommended Power	10 - 120 Watts
Transducer - Low Frequency Driver	5.25" Polypropylene Cone w/ Butyl Rubber Surround
Transducer - High Frequency Driver	1" Titanium Dome
Colors	Black, White
Grille - material	Powder-Coated Aluminum
Tweeter - part	1" Titanium Dome
Woofers/ Driver	5.25" Mineral-Filled Polypropylene w/ NBR Surround
Inputs	Gold-Plated 5-way Binding Posts
Height (SM = Height)	279.4 mm / 11"
Diameter (SM = Width)	171.5 mm / 6.75"
Weight	2.4 kg / 5.3 lb
Shipping Weight	5.9 kg / 13 lb
Regulatory - CE	approved
Regulatory - RoHS	approved

SPF-25

5.25" 2-Way Surface-Mount Outdoor Speaker



Description

Solaris speakers are built with a high-density resin enclosure, making the SPF-25 ideal for outdoor audio needs. With adjustable C-clamp hardware and standard OmniMount™ brackets, the SPF-25 mounts to any flat surface and features adjustable knobs to allow the speaker to swivel to an optimal listening range.

The SPF-25 incorporates a 5.25" polypropylene cone with butyl surrounds that create the full-bodied and responsive bass that gives music greater richness and impact, while the 1" titanium dome produces smooth and extended high frequencies.

Patented Rockustics Technologies

Rockustics and MSE Audio Group constantly develop new technologies that enhance audio product performance. Rockustics innovations are protected by multiple U.S. and international patents, which explicitly cover Rockustics dispersion, enclosure and dome technologies. MSE Audio Group actively

defends its patents in order to protect Rockustics resellers and end users.

Technical Data and Specification Tools

Technical Data

SoundTube Entertainment strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com.

Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for SoundTube speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are

collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Architectural Specifications

No specifications currently.

Rockustics

8005 W 110th Street, Suite 208
Overland Park, KS 66210
Phone 913.663.5600
Fax 913.663.3200
Toll Free (855) 663-5600
<https://rockustics.mseaudio.com>
All SoundTube products come with a 5-year limited warranty.

SPF-25

5.25" 2-Way Surface-Mount
Outdoor Speaker

