

CI15

3" Compact, Full-Range In-Wall Speaker



Specifications: CI15

Mounting hardware included

Nominal Impedance	8 ohms
Sensitivity dB @ 2.83V/1M	85.5 dB
Frequency Response (1)	115 Hz - 22 kHz
Recommended Power	5 - 60 Watts
Transducer - Full-Range Driver	3" Polypropylene w/ NBR Surround
Colors	Black or White
Enclosure alignment	Sealed
Grille - material	White ABS/Aluminum Paintable
Height (SM = Height)	127 mm / 5 in
Diameter (SM = Width)	127 mm / 5 in
Cutout Height (Surface Mount Height)	110.5 mm / 4.35"
Cutout Width/Diameter	110.5 mm / 4.35"
Cutout Depth	88.9 mm / 3.5"
Weight	1.4 kg / 3.1 lb
Shipping Weight	1.8 kg / 4 lb
Regulatory - UL	Approved UL1480A & UL2043
Regulatory - CE	approved
Regulatory - RoHS	approved

CI15

3" Compact, Full-Range In-Wall Speaker



Description

The CI15 is a full-range in-wall speaker. The CI15 features a sealed backcan, a visible footprint of 5 inches square and a low-profile ABS/aluminum grille, keeping the CI15 out of sight while the Speedwing™ mounting system makes installation easy. Along with its 3" polypropylene woofer, the CI15 features a 25/70.7/100 Volt transformer (bypassable for standard 8Ω operation).

Patented Phase Technology Technologies

Phase Technology and MSE Audio Group constantly develop new technologies that enhance audio product performance. Phase Technology innovations are protected by multiple U.S. and international patents, which explicitly cover Phase Technology dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Phase Technology resellers and end users.

Technical Data

and Specification Tools

Technical Data

Phase Technologies strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for Phase Technologies speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both

phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Architectural Specifications

No specifications currently.

Phase Technology

8005 W. 110th St. | Suite 208
Overland Park, KS 66210
Phone 9136635600
Fax
Toll Free 8556635600
<https://phasetech.mseaudio.com>
All Phase Technologies products come with a 5-year limited warranty.

CI15

3" Compact, Full-Range In-Wall Speaker



Optional Accessories

Pre-Construction Bracket (CI15-PCB)