

(800) 878-5789 • APC-Mfg.com

STANDARD COVER SYSTEM

2019 Order Form

Submit Form to: orders@apc-mfg.com or (317) 579-2006 fax

ODDED INCODMA	TION		,		○ Or	der	O Quote Only
ORDER INFORMATION  Distributor					TO NAME		
Dealer				SHIP TO NAME           Address			
Job Name PO#				City/State/Zip			
(Required)							
SHIP TO:		L TO METH					
		Pre-Paid (APC Preferred Carrier) Collect			RESIDENTIAL SHIPPING ADDRESS?		
- '		rd Party Collect					
		Other			(Nequireu	')	
JOB SPECIFICATION	ONS						
○ Under Track		○ Top Track			HOUSING TYPE:		Deck Mount (TT)
O Drilled O To	○ Flush Track			Recessed  ○ Wood		○ Vinyl Bench	
<ul><li>○ Encapsulation</li><li>○ Standard</li><li>○ 3 Channel Track</li></ul>		☐ U-Channel Needed			O Concrete		□White □Beige □Gray
☐ Deck on Deck ☐ Inverted Gunite		O Manual Choose One:			O Polymer Box (APC) Other		<ul><li>○ Bench Ends Only</li><li>□ White □ Beige □ Gray</li></ul>
Choose One:	O Preship U-Channel			Choose One:		O Bench Frame Only	
OPreship Encapsulation	○ Ship U-Channel with System		em	O Preship Polymer Box		○ No Bench or Frame	
○ Ship Encapsulation with	○ Not Needed			○ Ship Polymer Box w/System ○ Not Needed		n   O No Bonoir or Framo	
O Not Needed			_				
CONTROLLER:					TRACK SPACE:	LID TYPE:  O Aluminum Lid (Standard)	
		Inches	Including Steps		Width		num Lid (Standard)
○ 2nd Controller	Std: 12" / Max: 24"		ft. Xft.		ftin.		-0374 (24"x16"x1.5" w/strap)
MOTOR TYPE:		3	For exterior steps, include drawing		Length	☐ MC-0509 (24"x16"x .1.5" w/o strap)	
Standard		1	DOOL LOGATION	-	ft.		-0549 (24"x13"x 1/g") ed Flush Lid (w/APC Polymer)
☐ High Torque			POOL LOCATION Outdoor	÷		□ Ne	
O Spa (max 10' x 25')	O COVER BO		Olndoor				Flush Lid Riser □ Needed
O Hydraulic	Left	Right				O Other	
		RIC COLOR:  avv Blue O Brown		<u> D</u>	ROP TO WATER:		ADDITIONAL MATERIALS:
		avy Blue					<ul><li>Lid End Protectors</li><li>Ladder Hinges</li></ul>
		Light Blue		-			O System Bonding Kit
O Atlas Bracket: 12 - 16"Qty O B		Beige Charcoal					○ Rope Reel Protectors
O Atlas Bracket: 16 - 20"Qty Lead		d Edge Loop ○ Yes ○ No		<u>s</u>	OLAOIX.		O Re-Usable Form - Bullnose
Acry Atlas Bracket: 20 - 24" Qty Acry		/lic O Yes O No			· · · · · · · · · · · · · · · · · · ·		<ul><li>○ Re-Usable Form - 90°</li><li>○ 2nd Wayne Pump</li></ul>
	ing Wire O Yes ONo		- 2	7" Slack Standard for TT		2 End Wayno i unip	
COMMENTS/SPECIAL INSTRUCTIONS:							
<u>}</u>							